

# Declared Product Performance

## Batten step

- 1 Construction product's designation and trade name:  
**Product kit for fixed batten step for tiled roofs in accordance with the system: Batten step**
- 2 Construction product type designation(s) per constituent component:
- **Batten step 2-bulge concrete. 1" C-C 300**
  - **Batten step 2-bulge concrete. 2" C-C 300**
  - **Batten step 2-bulge clay / 1-bulge concrete 1" C-C 240**
  - **Batten step 1-bulge clay 1" C-C 220**
  - **Batten step C-C 300 unbent straight**
  - **Batten step combi 5 pcs**
  - **Batten step 2-bulge concrete C-C 300**
  - **Batten step 2-bulge clay / 1-bulge concrete C-C 240**
  - **Batten step 1-bulge clay 1" C-C 220**
- 3 Construction products intended use
- **Access device on tiled roof**
- 4 Manufacturer's name and contact address  
**CW Lundberg Industri AB - Landsvägen 52, Box 138, 792 22 Mora, Sweden**
- 5 Authorised representative, if such has been appointed:  
**CW Lundberg Sp. z o.o. - ul. Strefowa 9, 58-200 Dzierżoniów, Polska**
- 6 Assessment and inspection of performance:  
**Assessment and ongoing inspection is conducted by the supervisory body, as well as through in-house inspections.**
- 7 Technical specification:  
**Accredited certifying body RISE, Research Institutes of Sweden  
Certificate 12 71 01**
- Applied technical specification: EN 12951:2004**

- 8 Construction product performance:

Essential characteristics	Performance	Remarks
Mechanical strength (class 1 according to 6.1) - Static load	Fulfils	
Corrosion resistance	Fulfils	
External fire impact	B <sub>roof</sub>	

- 9 Performance for the aforementioned product complies with the product performance as indicated in Section 8. This document is issued at the manufacturers own responsibility according to Section 4.

Signed on behalf of the manufacturer by:



Thomas Lundberg  
Managing Director

Mora, 16 January 2024



---

**The product's performance as stated below does not constitute a part of the declared product performance. The manufacturer provides supplemental information about the product that affects or may affect its use.**

*Installation of batten step for tiled roofs is done in accordance with installation instructions M-034 and M-081.*

*Products can be selected in various colours of powder coating for design.*

Other Performance

<i>Characteristics</i>	<i>Performance</i>	<i>Technical specifications</i>
Corrosion resistance (corrosivity class C4)	40 years	EN ISO 12944-2