

Declared Performance of the Product

Façade Ladder with Back Guard

- 1 Designation and trade name of the construction product:
Product kit for the installation of façade ladder in accordance with the system: Façade ladder
- 2 The construction product's type designation/names per constituent component:
- **Roof/façade ladder 1.5 m / 2.4 m**
 - **Extension kit, roof/façade ladder**
 - **Bracket kit A-220 / A-400 / A-500 / A-600 / A-800 / A-1000**
 - **Mounting plate façade ladder**
 - **Handrail for façade ladder 1280 mm**
 - **Foldable landing façade ladder compl. 390 x 410 mm**
 - **Standing plate façade ladder excl. screw 300 x 440 mm**
 - **Bracing kit for handrail adjustable**
 - **Back guard brace for façade ladder iØ 650 mm**
 - **Bracing kit, back guard 900 mm**
- 3 Intended Use for the Construction Product:
- **Access to roof via façade**
 - **Attachment of personal fall protection equipment**
 - **Back guard (protective cage)**
 - **Landing, foldable**
 - **Standing plate**
 - **Installation on intended façade types according to specification page 2**
- 4 Manufacturer's Name and Contact Address:
CW Lundberg Industri AB
Landsvägen 52, Box 138, 792 22 Mora, Sweden
- 5 Authorised representative if such has been appointed: **Not applicable**
- 6 Assessment and inspection of performance:
Assessment and continual inspection performed by supervisory body, and in-house inspections.
- 7 Technical specifications:
Supervisory body, Research Institutes of Sweden (RISE)
Certificate 12 71 01

Applied technical specification SS 831340

- 8 Construction product's performance:

Essential properties	Performance	Remarks
Mechanical strength		-
- Static load (according to 6)	Satisfies	
Dimensions (according to 5)	Satisfies	
Corrosion resistance (according to 7)	Satisfies	

- 9 Performance of the product for the aforementioned product is consistent with the Performance of the product specified in Section 8. This document is issued at the responsibility of the manufacturer in accordance with Section 4.

Signed on behalf of the manufacturer by:



Thomas Lundberg
Managing Director

Mora, 30 April 2024



The product information stated below does not constitute a portion of the declared Performance of the product. The manufacture issues additional information about the product which affects, or which may affect its use.

Installation of façade ladder on wood or sheet metal façades is done in accordance with Installation Instruction M-130. For other façade materials, use the screw joints according to the conditions of the façade as set out in M-302.

Products can be selected in various colours of powder lacquer for design.

Other Performance

<i>Properties</i>	<i>Performance</i>	<i>Technical specifications</i>
Corrosion resistance (corrosivity class C4)	40 years	EN ISO 12944-2
Exterior reaction to fire (according to 7.3)	B _{roof}	EN 516:2006